



M5 CAP HEAD SCREWS PROVIDED

- 1 OFF 16 LONG
- 2 OFF 25 LONG

MATERIAL : 30% GLASS FILLED NYLON

MAX. SERVICE TEMP. : 110°C LONG TERM.
200°C SHORT TERM.

MIN. SERVICE TEMP. : -20°C

RECOMMENDED MINIMUM No. OF BRACKETS	
TRANSUCERS UP TO ±10mm STROKE	1
TRANSUCERS WITH STROKE OF ±12.5mm OR MORE	2

E	DCS20/51 (AAP2158)		4.1.17
D	DCS77/46		14.1.13
C	DCS26/46		24.7.12
B	DCS93/45 (AAP2044)		15.12
A			8.3.12
No	DESCRIPTION	APP'D	DATE
ALTERATIONS			

RDP ELECTRONICS LTD, WOLVERHAMPTON

OWNS THE INTELLECTUAL COPYRIGHT ON THIS INFORMATION
IT MUST NOT BE DUPLICATED OR DISTRIBUTED IN ANY FORM
WITHOUT PERMISSION OF RDP ELECTRONICS LIMITED

MOUNTING BLOCK MODEL MB01 FOR LVDT TRANSDUCER

DRAWN	R. LATHAM	
SCALE	2:1	A3
DATE	8.3.12	
APPROVED		
DRAWING No	D19591	1 of 1