


DCWL Submersible DC to DC LVDT Displacement Transducer

- High accuracy
- High cycle life
- Submersible
- Stainless steel
- Infinite resolution
- Supply 6 to 18V, output $\pm 2.2V$
- Supply/output isolation



These transducers are for displacement / position measurement. They make an accurate position measurement of the movement of the armature (the sliding part) relative to the body of the displacement transducer.


This transducer uses the Linear Variable Differential Transformer (LVDT) principle which means that it is probably the most robust and reliable position sensor type available. The strength of the LVDT sensor's principle is that there is no electrical contact across the transducer position sensing element which for the user of the sensor means clean data, infinite resolution and a very long life.

Our DC to DC LVDT transducer has all of the benefits of the LVDT sensor principle with the added convenience of built-in LVDT electronics enabling a dc supply and dc output.

Our submersible displacement transducers are designed to make measurements whilst submerged in suitable liquids. Fluids which are non-magnetic can be allowed to flood the armature tube without affecting the operation of the transducer.

Unguided version.

DCWL500 to DCWL8000




- CL1=62mm
- D1=20.6mm ± 0.12 mm
- D3=4.75mm
- D4=5.97mm
- ID=6.80mm
- TF=M5x0.8, 15mm
- X=Centre of range

On our DCWL unguided LVDTs the armature assembly is a separate component, to make a measurement the user must guide the armature inside the body without touching the sides. Our DCWL unguided position measurement transducers are appropriate where external guidance is available and give truly non-contact operation

Type	Range	Linearity error (% F.S.)	L	X (nom)	Total weight	Armature weight	Inward over-travel
DCWL500	± 12.5 mm	$\pm 0.5/\pm 0.25/\pm 0.1$	203mm	38mm	243g	19g	10mm
DCWL1000	± 25 mm	$\pm 0.5/\pm 0.25/\pm 0.1$	231mm	63mm	300g	26g	23mm
DCWL2000	± 50 mm	$\pm 0.5/\pm 0.25/\pm 0.1$	354mm	76mm	399g	40g	10mm
DCWL3000	± 75 mm	$\pm 0.5/\pm 0.25/\pm 0.1$	470mm	114mm	527g	57g	23mm
DCWL4000	± 100 mm	$\pm 0.5/\pm 0.25/\pm 0.1$	503mm	127mm	655g	71g	10mm
DCWL6000	± 150 mm	$\pm 0.5/\pm 0.25$	707mm	178mm	882g	104g	10mm
DCWL8000	± 200 mm	$\pm 0.5/\pm 0.25$	909mm	254mm	1.3kg	142g	36mm

Captive guided version.




CL1=62mm
 D1=20.6mm ±0.12mm
 D3=4.75mm
 TF=M5x0.8, 15mm
 X=Centre of range

Our DCWL captive guided displacement transducer has bearings to guide the armature inside the measurement sensor. Our DCWL captive LVDTs are for position measurement applications where guidance may be poor and end bearings may be required.

Type	Range	Linearity error (% F.S.)	L	X (nom)	Total weight	Inward over-travel	Outward over-travel
DCWL500B	±12.5mm	±0.5/±0.25/±0.1	203mm	38mm	370g	10mm	28mm
DCWL1000B	±25mm	±0.5/±0.25/±0.1	231mm	63mm	428g	17mm	25mm
DCWL2000B	±50mm	±0.5/±0.25/±0.1	354mm	76mm	541g	10mm	28mm
DCWL3000B	±75mm	±0.5/±0.25/±0.1	470mm	114mm	655g	23mm	28mm
DCWL4000B	±100mm	±0.5/±0.25/±0.1	503mm	127mm	797g	10mm	28mm
DCWL6000B	±150mm	±0.5/±0.25	707mm	178mm	1.1kg	10mm	35mm
DCWL8000B	±200mm	±0.5/±0.25	909mm	254mm	1.5kg	36mm	41mm
DCWL10000B	±250mm	±0.5/±0.25	1094mm	305mm	1.7kg	36mm	47mm
DCWL15000B	±380mm	±0.5	1493mm	406mm	2.2kg	10mm	28mm
DCWL18500B	±470mm	±0.5	1766mm	508mm	2.6kg	23mm	35mm

Spring return version.

DCWL500A to DCWL3000A



CL1=62mm
 D1=20.6mm ±0.12mm
 D3=4.75mm
 X=Centre of range

Our DCWL spring displacement transducer has bearings to guide the armature inside the measurement sensor and a spring which pushes the armature to the fully out position. Our DCWL spring return LVDTs are appropriate where it is not possible to connect the transducer armature to the moving component being measured.


Type	Range	Linearity error (% F.S.)	L	X (nom)	Total weight	Spring force at X	Spring rate	Inward over-travel	Outward over-travel
DCWL500A	±12.5mm	±0.5/±0.25/±0.1	203mm	38mm	257g	1.2N	0.2N/cm	6mm	28mm
DCWL1000A	±25mm	±0.5/±0.25/±0.1	231mm	63mm	314g	1.9N	0.3N/cm	4mm	25mm
DCWL2000A	±50mm	±0.5/±0.25/±0.1	354mm	76mm	428g	4.1N	0.4N/cm	6mm	28mm
DCWL3000A	±75mm	±0.5/±0.25/±0.1	470mm	114mm	541g	5.4N	0.4N/cm	15mm	28mm

Options And Accessories

Rod-end bearings for captive-guided position transducers





Mounting block



Torque
 Position
 Pressure
 Load Cells
 Displacement
 Instrumentation


Electrical termination options

Standard cable - End exit connector with cable fitted




Cable length = 5m
 Operating temperature range* = -25°C to 90°C
 Maximum static pressure* = 1000kPa
 CL1 = 62mm

Cable Option 1 - End exit solder pins for customer to fit their own cable




Operating temperature range* = -40°C to 125°C
 CL1 = 21mm
 CL2 = 6.4mm
 CD1 = 12.7mm

Cable Option 2 - End exit fully sleeved integral cable




Cable length = 600mm to 7m
 Operating temperature range* = -40°C to 100°C
 Maximum static pressure* = 3MPa
 CL1 = 25mm
 CD1 = 25mm
 CL2 = 51mm
 CBD = 184mm

Cable Option 3 - End exit part-sleeved integral cable




Cable length = 1m to 100m
 Cable sleeve length = 600mm
 Operating temperature range* = -40°C to 90°C
 Maximum static pressure* = 2MPa
 Cable sleeve length = 600mm
 CL1 = 25mm
 CL2 = 51mm
 CD1 = 25mm
 CBD = 184mm

Cable Option 5 - End exit integral MI (mineral insulated) stainless steel cable




Cable length = 100mm to 70m
 Operating temperature range* = -40°C to 200°C
 Maximum static pressure* = 21MPa
 CL1 = 4mm
 CD1 = 3.0mm
 D5 = 11.7mm

Cable Option 6 - End exit connector with customer defined cable length fitted



Cable length = 0mm to 1000m
 Operating temperature range* = -25°C to 125°C
 Maximum static pressure* = 800kPa
 CL1 = 64mm


Cable Option 7 - Side exit connector with cable fitted



Cable length = 5m
 Operating temperature range* = -25°C to 90°C
 Maximum static pressure* = 1000kPa
 TR = M5x0.8, 11mm
 CL1 = 64mm
 CBX = 25mm


Electrical termination options

Cable Option 8 - Side exit fully sleeved integral cable




- Cable length = 600mm to 7m
- Operating temperature range* = -40°C to 100°C
- Maximum static pressure* = 3MPa
- TR = M5x0.8, 11mm
- CBD = 184mm
- CBX = 25mm
- CD1 = 25mm
- CL1 = 30mm
- CL2 = 55mm

Cable Option 9 - Side exit connector with customer defined cable length fitted





- Cable length = 0mm to 1000m
- Operating temperature range* = -25°C to 125°C
- Maximum static pressure* = 800kPa
- TR = M5x0.8, 11mm
- CBX = 25mm
- CL1 = 72mm

Cable Option 10 - Side exit part-sleeved integral cable



- Cable length = 600mm to 1000m
- Cable sleeve length = 150mm
- Operating temperature range* = -40°C to 90°C
- Maximum static pressure* = 2MPa
- TR = M5x0.8, 11mm
- CBD = 184mm
- CBX = 25mm
- CD1 = 25mm
- CL1 = 30mm
- CL2 = 55mm

Cable Option 11 - Side exit part-sleeved integral cable and conduit fitting



- Cable length = 1m to 1000m
- Cable sleeve length = 150mm
- Operating temperature range* = -40°C to 90°C
- Maximum static pressure* = 2MPa
- TR = M5x0.8, 11mm
- TC = 1/2"-14 NPT, 20mm
- CBD = 184mm
- CBX = 25mm
- CL1 = 25mm
- CL2 = 50mm
- CSL = 150mm

Specification *Transducer and cable option specifications should be compared and the worst figures used	
Supply voltage (Vs)	6V to 18V dc, 60mA typical
Output	±2.2V
Output ripple	30mV (peak-to-peak)
Analogue output bandwidth	200Hz (flat)
Output impedance	2 Ohms
Linearity error (Standard)	±0.5% F.S.
Linearity error (Optional on some models)	±0.25% F.S.
Linearity error (Optional on some models)	±0.1% F.S.
Temperature coefficient (span)	±0.03% F.S. /°C (typical)
Operating temperature range	-40°C to 70°C
Maximum static pressure	21MPa*



Due to our policy of on-going development, DCWL specifications may change without notice. Any modification to our DCWL may affect some or all of the specifications for our equipment. All DCWL dimensions and specifications are nominal.

DCWL - WARNING - PERSONAL INJURY

Do not use our DCWL as safety, emergency stop or feedback devices in any application where the failure of this product could result in damage to equipment, personal injury or death.

USA & Canada
 RDP Electrosense
 2216 Pottstown Pike
 Pottstown, PA 19465
 USA
 Tel: 610-469-0850
 Tel: 800-334-5838
 Fax: 610-469-0852
 Email: info@rdpe.com

Global Head Office
 RDP Electronics Ltd
 Grove Street, Heath Town
 Wolverhampton, West Midlands, WV10 0PY
 United Kingdom
 Tel: +44 1902 457512
 Email: sales@rdpe.com
 URL: www.rdpe.com

Torque
 Position
 Pressure
 Load Cells
 Displacement
 Instrumentation